

▼ Shown: **PMU-10427**



- Powerful two-speed pump is lightweight and easy to carry
- Standard heat exchanger package keeps pump cool under extreme use
- Glycerine filled gauge with scales reading in psi and bar
- Transparent overlays in Ft.lbs and Nm for all Enerpac torque wrenches provide a quick torque reference
- Universal motor for a high power-to-weight ratio; generates full pressure on as little as 50% of the rated line voltage
- Adjustable pressure relief valve for accurate torque adjustments and precise repeatability
- Fitted with polarized safety lock-ring couplers

PMU Series



Reservoir Capacity:
0.5 gallon

Flow at 10,000 psi:
20 in³/min

Maximum Operating Pressure:
11,600 psi

Motor Size:
0.5 hp



Twin 3.5:1 Safety Hoses

Use Enerpac THC-700 series twin 3.5:1 safety hoses with double-acting wrenches to ensure the integrity of your

hydraulic system.

19.5 feet long, 2 hoses	THC-7062
39 feet long, 2 hoses	THC-7122



Glycerine Filled Gauges

All Enerpac torque wrench pumps feature a glycerine filled gauge. The pressure sensing parts are sealed and

dampened by glycerine for prolonged life.



Gauge Overlay Kit GT-4015

Gauge overlay kits are available separately. Includes overlays for all SQD and HXD torque wrenches.

▼ PERFORMANCE CHART

Maximum Pressure Rating (psi)		Oil Flow Rate (in ³ /min)		Model Number	Useable Oil Capacity (gal)	Electric Motor	Dimensions L x W x H (in)	Weight (lbs)
1 st stage	2 nd stage	1 st stage	2 nd stage					
700	11,600	200	20	PMU-10427	.50	115V- 1 ph -50/60Hz	17 x 11 x 15	53
700	11,600	200	20	PMU-10422	.50	230V- 1 ph -50/60Hz	17 x 11 x 15	53